

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Yamalube Chain Lubricant Spray**

Article number: YMD-65049-A0-12, YMD-65049-A0-21, YMD-65049-A0-22

1.2 Relevant identified uses of the substance or mixture and uses advised against Void

Application of the substance / the mixture Maintenance product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Yamaha Motor Europe N.V.

Koolhovenlaan 101

NL-1119 NC Schiphol-Rijk

Tel.: +31 (0) 20 6546000

Fax: +31 (0) 20 6546565

www.yamaha-motor.eu

P&Acustomersupport@yamaha-motor.nl

Further information obtainable from: Nationaal Vergiftigingen Informatie Centrum Utrecht

1.4 Emergency telephone number: +31 (0) 30 2748888

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms GHS02, GHS07, GHS09

Signal word Danger

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 1)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of the substances with nonhazardous additions.

· **Dangerous components:**

| | | |
|---|---|---------|
| CAS: 64742-49-0 921-024-6 Reg.nr.: 01-2119475514-35 | Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 25-50% |
| CAS: 106-97-8 EINECS: 203-448-7 | butane ⚠ Flam. Gas 1, H220; Press. Gas C, H280 | 20-<25% |
| CAS: 74-98-6 EINECS: 200-827-9 | propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280 | 20-<25% |

- **SVHC** None
- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Take affected persons out into the fresh air.
If symptoms persist consult doctor.
- **After inhalation:**
Supply fresh air.
Seek medical treatment in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Hazards** If swallowed or in case of vomiting, danger of entering the lungs.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 3)

MT

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 2)

- **Additional information**
Danger of bursting.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources.
Ensure adequate ventilation
Avoid contact with skin and eyes.
- **6.2 Environmental precautions:**
Do not allow to penetrate the ground/soil.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Avoid contact with skin and eyes.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

-MT-

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 3)

· **DNELs****64742-49-0 Naphtha (petroleum), hydrotreated light**Inhalative | DNEL system. effects (long-term) | 2035 mg/m³ (Worker)· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not necessary if room is well-ventilated.· **Protection of hands:**

Preventive skin protection by use of skin-protecting agents is recommended.

After each cleaning use treatment creams, for very dry skin greasy ointments.

· **Material of gloves** Not required.· **Penetration time of glove material** Not required.· **Eye protection:** Not required.**SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Aerosol**Colour:** Light brown· **Odour:** Characteristic· **Odour threshold:** Not determined· **pH-value:** Void· **Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** -44 °C· **Flash point:** -97 °C· **Ignition temperature:** 365 °C· **Self-igniting:** Product is not selfigniting.· **Danger of explosion:** Heating may cause an explosion.
In use, may form flammable/explosive vapour-air mixture.· **Explosion limits:****Lower:** 1,5 Vol %**Upper:** 10,9 Vol %· **Vapour pressure at 20 °C:** 8300 hPa· **Density:** Not determined.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:****Dynamic:** Not determined**Kinematic:** Not determined

(Contd. on page 5)

-MT-

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 4)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Store away from oxidising agents.
- **10.6 Hazardous decomposition products:**
No decomposition if used and stored according to specifications.
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

| | | |
|---|----------|-------------------|
| LD/LC50 values relevant for classification: | | |
| 64742-49-0 Naphtha (petroleum), hydrotreated light | | |
| Oral | LD50 | >5840 mg/kg (rat) |
| 106-97-8 butane | | |
| Inhalative | LC50/4 h | 658 mg/l (rat) |

- **Specific symptoms in biological assay:** Not determined
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish

(Contd. on page 6)

-MT

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 5)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations.

· **European waste catalogue**

16 05 04* gases in pressure containers (including halons) containing hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

| | |
|--|--|
| · 14.1 UN-Number · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT Aerosols, flammable |
| · 14.3 Transport hazard class(es) · ADR · Class · Label | 2 5F Gases. 2.1 |
| · IMDG, IATA · Class · Label | 2.1 2.1 |
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): | Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light Yes Symbol (fish and tree) Symbol (fish and tree) |
| · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code · Segregation Code | Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 |

(Contd. on page 7)

MT

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 6)

| | |
|--|--|
| . | except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1 |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
Flam. Gas 1: Flammable gases, Hazard Category 1
Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas C: Gases under pressure: Compressed gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

(Contd. on page 8)

MT

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 08.03.2016

V - 5

Revision: 08.03.2016

Trade name: Yamalube Chain Lubricant Spray

(Contd. of page 7)

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
· *** Data compared to the previous version altered.**

MT