

e24 0148 (9)



Street-legal component approval certificate

for non-original motorcycle exhaust system



503131

Approval No.:	e24*97/24*2009/108/9/III*0148*04
Issued by:	NATIONAL STANDARDS AUTHORITY OF IRELAND Certification Services - Operations Manufacturing 1 swift Square, Northwood, Santry, Dublin 9, Ireland
Place & date of type-approval:	Dublin, 17.02.2012
Report No.:	II-00025-CM-GBM-04
Issued by:	TÜV SÜD AUTOMOTIVE GMBH TÜV SÜD Gruppe DE-85748 Garching
Date of issue:	14.02.2012
Approval identification:	e24 0148 (9)

Type and version of exhaust: M-HR027 / M-HR02702T, M-HR02702SS, M-HR02703T, M-HR02703SS, M-HR0270IT, M-HR0270ISS, M-HR02704T, M-HR02704SS, M-HR02705T, M-HR02705SS.

Marking: Engraved by laser / plate fixed with rivets.

Field of application:

Manufacturer	Commercial description	Vehicle type (and no. of homologation)	Engine type	Component parts, dimensions in mm	Dimensions of the part in mm or original part / replacement part	Akrapovic part no. Or homologation no.		
PIAGGIO & C.S.p.A.	Vespa GTS 300i	M45 (e3*0306*)	M454M	Header pipes	Original part	H-xxx L-xxx		
	Vespa GTS 250i		M451M	Header pipes				
	Vespa GTV 250i		M451M	Link pipe	ø 62 x 65	P-KAT-028 e24*0150*(5) M-HR027 e24*0148*(9)		
	Vespa GTS 125i	M455M	Catalytic converter					
	Beverly 300i	M69 (e3*0570*)	M692M	Silencer	Hexagonal 110 x 140			
	Beverly 125i		M691M	Outlet pipes ø 22				
	Carnaby 125	M60 (e3*0459*)	M28FM		Length without end caps 350			
	Carnaby 200		M601M					
	Carnaby 250		M603M					
	Carnaby Cruiser 300	M64 (e11*0794*)	M604M					
	MP-3 250 LT		M632M					
	MP-3 300 LT		M633M					
	MP-3 300 LT	M72 (e3*0572*)	M634M					
	MP-3 300 LT Hybrid		M652M					
	MP-3 300 Yourban LT	M75 (e3*0578*)	M712M					
	MP-3 125(X2)	M47	M473M					
	MP-3 250(X2)	M47 (e11*0433*)	M472M					
	MP-3 125		M631M					
	MP-3 250	M63 (e11*0761*)	M632M					
	MP-3 300		M633M					
	MP-3 300		M634M					
	MP-3 125 Hybrid	M65 (e3*0555*)	M651M					
	MP-3 125 Yourban		M71M					
MP-3 300 Yourban	M71 (e3*0577*)	M712M						
HONDA (I)	SH 300i	NF02 (e3*0447*)				NF02E		
	SH 125i	JF14 (e3*0208*)	JF14E					
	SH 125i	JF23 (e4*2115*)	JF14E					
	SH 150i	KF08 (e3*0297*)	KF08E					
	PS 125i	JF17 (e3*0400*)	JF14E					
	PS 150i	KF09 (e3*0401*)	KF08E					
GILERA	Nexus 250	M35 (e3*0402*01)	M353M					
	Nexus 125	M35 (e3*0402*03)	M357M					
	Nexus 300	M35 (e3*0402*05)	M356M					
	Runner 125	M46 (e3*0338*)	M461M					
			M463M					
			M462M					
Runner 200		M464M						
APRILIA	Sportcity 125 ONE / CUBE	VB (e11*0118*)	M281M					
	Sportcity 200 CUBE		M287M					
	Sportcity 250 CUBE		M282M					
	Sportcity 250 CUBE		M288M					
	Sportcity 300 CUBE		M281M					
DERBI	GPI 250	PT (e8*0071*)	M237M					
Thai HONDA	CBR 250 R	MC41 (e13*0457*)	MC41E					
	CBR 125 R	JC50 (e13*0445*)	JC50E					

To be filled out by Akrapovič representative:

Date of purchase: Issued by:

Stamp & signature:

Muffler repack kit service intervals

The durability of the damping material depends on the type of motorcycle, riding style, mileage etc. Normally, single and twin cylinder engines produce a stronger exhaust gas wave pulse and a higher temperature. Often, riding on a race track requires noise control. The insulating material should be replaced when you notice any visual changes on the muffler sleeve material or when the muffler exceeds the noise limit. Please check the muffler visually before every season.

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Maintenance

1. Clean the titanium muffler outer sleeves with a multi-purpose spray lubricant (WD-40 or equivalent) and carbon-fiber outer sleeves with soft and dry cloth. Do not use aggressive chemical cleaners, because they can damage the sticker. A change in the color of the exhaust system is normal due to the high temperatures.

2. The wearing out of the muffler silencing material depends on the type of the motor and riding style. Contact your dealer/serviceman if visible changes appear on muffler's outer sleeve or the noise level is increased.

3. Periodically make sure all the bolts are sufficiently tight.

Exclusion of Certain Liability

1. The manufacturer, importer or dealer shall not be liable for any incidental damage including personal injury or any other damages caused by improper installation or operation of the Akrapovič exhaust system. When installing the Akrapovič exhaust system be careful that the exhaust system does not touch other parts sensitive to high temperature.

2. Akrapovič makes no representation or warranties with regard to damage caused by the improper installation, use and maintenance of the Akrapovič exhaust system. The warranty is limited to defects recognized by our technical department and to normal use, and excludes items subject to normal wear (gaskets and damping wool). The guarantee is void in case of accident, modification, improper or competition use.

3. Do not attempt to install the Akrapovič exhaust system on a motorcycle for which it was not made or tested by Akrapovič.

4. When the exhaust system gets very hot during operation, be careful not to burn yourself on the exhaust system or parts which are in direct contact with it, even when the motor is not running. Also protect other people, especially children, from the injuries mentioned above.

5. In some cases Akrapovič exhaust system kits contain chemical products (ceramic anti-seizing grease). Handle with care, do not inhale or swallow. Avoid excessive contact with skin, eyes or mucous membranes. Keep out of the reach of children.

6. Technical specifications of Akrapovič exhaust systems and related products subject to change without notice.